

Technical specifications:

- Rated voltage/current:
3P 300V/13A
4P 300V/13A
5P 300V/9A
- Degree of protection:IP67
- Temperature range:-25°C~+80°C
- Mating cycles:≥500
- Contact resistance:≤5mΩ

Order NO. Description

78023 - XX - X - XXXX

POLES

- 03=3Poles
- 04=4Poles
- 05=5Poles

CABLE LENGTH(cm)

- 30=30cm
- 100=100cm
- 1000=1000cm

CABLE SHEATH

- C=PVC
- R=PUR

Pin Assignment

Pin layout	3PIN	4PIN	5PIN
Wire gauge	18AWG	18AWG	20AWG
PIN1	GN/YE	Black	Black
PIN2	Brown	Blue	Blue
PIN3	Blue	Brown	GN/YE
PIN4		White	Brown
PIN5			White


No.	PART NAME	DESCRIPTION	Q'TY
5	Cable	AWG18/20 3~5C,PVC OR PUR ,Black	1
4	Molding	PVC ,Black	1
3	Nut	ZINC; Nickel plated	2
2	Housing	TPU,Black	2
1	Contact	Male pin,Brass; Gold-plated	6~10

-TOLERANCES-
UNLESS OTHERWISE
SPECIFIED

UNLESS OTHERWISE SPECIFIED
TOLERANCES FOR MILLIMETERS ARE:
0.5 - 8mm ± 0.20mm
8 - 30mm ± 0.25mm
30 - 120mm ± 0.30mm



RENHOTEC GROUP



PART DESCRIPTION:
Double R/A 7/8" male, Molding type

Appr:	JIM.KING	P/N: 78023-XX-X-XXXX				
Check:	Date	Scale	Unit	Type	Page	
Draw:	DING	2022.12.06	Free	MM	Z 1/1	